

SN-NVR3632E4-P16

32CH 1.5U 4HDD 16CH PoE 4K NVR




Key Features

- Up to 32ch IP cameras access
- Up to 12MP resolution recording
- 4 SATA hard disk each up to 12TB
- 1 RJ45 10M/100M/1000M network interface
- Plug & play with 16ch PoE interfaces
- Support RAID 5/6/10
- Smart search & playback
- Support cloud upgrade

Specification

Video Input		Storage	
IP Camera Input	32 Channel	HDD	4 SATA Ports, up to 12TB for each HDD
Incoming Bandwidth	320Mbps	eSATA	1 eSATA Port
Outgoing Bandwidth	320Mbps	Cloud Storage	Support
Video Output		Disk Array	
HDMI Output	3840×2160,1920×1080, 1440×900, 1280×1024	Array Type	RAID 5, RAID 6, RAID 10
VGA Output	1920×1080, 1440×900, 1280×1024	Interface	
Different Source Output	Support	Interface	1 × RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
Decoding Capacity	1ch 12MP, 4ch 8MP, 8ch 4MP, 16ch 1080P, 32ch 720P	PoE	16 Ports (IEEE 802.3af), 128W
Dual Stream	Support	HDMI	1
Multi-screen Display	1st Screen: 1/4/8/9/16/32/36 2nd Screen: 1/4/8/9/16	VGA	1
Recoding		Audio I/O	1/1
Resolution	12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1 etc.	Alarm I/O	2/2
Recording Mode	Manual, Schedule (Regular, Continuous), Event	USB	3 ports (USB 2.0 × 2, USB3.0 × 1)
Trigger Events	Motion Detection, Video Loss, Alarm in, IVS	General	
Playback and Backup		Power Supply	AC100 ~ 240V
Sync Playback	16/9/4/1	Power Consumption	< 15 W (without HDD)
Search Mode	Time /Date, Alarm, Picture grid, Event	Operating Conditions	-10 °C ~ 50 °C (14 °F ~ 122 °F)
Backup Mode	USB Device, Network, eSATA	Storage Conditions	Less than 90% RH
Alarm		Certifications	CE/FCC
General Alarm	Motion Detection, Video Loss, IVS, Alarm in, Alarm out	Dimensions	440 × 368.3 × 70 mm (17.32 × 14.5 × 2.76 inch)
Abnormal Alarm	Disk Alarm, IP Address Conflict, Network Disconnect	Net Weight	4.65 kg (10.25 lb) without HDD
Network			
Network Function	HTTP, HTTPS, TCP/IP, IPv4, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP, 3G/4G, PPPoE		
Remote Users	8 users		
Smart Phone	iPhone, iPad, Android		
Interoperability	ONVIF, SDK, CGI		www.sunellsecurity.com

Dimensions (mm)



Rear Panel



©2022 Sunell all rights reserved. Design and specifications are subject to change without notice.